SUPER TWO STROKE

Last Updated: 09.01.2025
Product Code: AE0477

SUPER TWO STROKE is a high performance, semi synthetic two stroke oil which utilises the very latest low ash additive technology, together with a balanced combination of synthetic and highly refined mineral base oils to meet the severe requirements of JASO FD specification, as well as modern demands for a low smoke, multi-purpose oil suitable for use in a variety of applications.

APPLICATION

Latest technology makes it suitable for both air- and water-cooled two stroke engines in modern scooters, mopeds and motorcycles, and is compatible with both pre-mix and oil injection systems. The balanced formulation makes it also suitable for use in a wide variety of other applications such as chainsaws, lawnmowers etc.

Can be mixed with petrol in ratios between 1:75 and 1:25, but please follow equipment manufacturer guidelines and recommendations.

BENEFITS

- Modern, very low-smoke formulation
- Conforms to the strict requirements of JASO FD specification, with far higher detergent levels than JASO FC
- Higher detergency reduces combustion chamber deposits to prevent power loss and pre-ignition
- Enhanced protection against cylinder and piston scuffing
- Very high film strength for ultimate engine protection

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- JASO FD
- API TC
- ISO-L-EGD

TYPICAL PROPERTIES

Appearance	Red
Kinematic Viscosity @ 100°C	6.95
Specific Gravity @ 15.6°C	0.872
Flash Point °C	140

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963