

SUPERTEC 15 is medium to long term rust preventative which leaves a thin protective film giving excellent indoor storage protection and also for components stored covered outdoors.

APPLICATION

Use as received – apply by spray, brush or dipping in a well-ventilated area. Leaves a thin waxy film on drying.

For best results apply sparingly to avoid excessive product build-up.

BENEFITS

- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces.
- Compatible with both ferrous and non-ferrous metals.
- Outstanding corrosion protection properties.
- Excellent penetration qualities.
- Non-staining formulations.
- Provide medium to long term protection of metal components when stored undercover.
- Ideal for protection of metal stocks, agricultural machinery etc.

PERFORMANCE PROFILE

Indoor Protection	6 Months
Outdoor Protection Covered	1 Month
Outdoor Protection Uncovered	Not Recommended

TYPICAL PROPERTIES

Appearance	Amber fluid
Specific Gravity @ 15°C	0.809
Flash Point (COC) °C	38
Non-volatile residue	17%
Film Thickness	20 microns

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.