

SUPERTEC 93 EXTRA

Last Updated: 09.01.2025
Product Code: IP0535

S|AIR Lubricants

SUPERTEC 93 EXTRA is a long term rust preventative which leave a thin protective film giving excellent indoor storage protection for over 30 months and outdoor of over 18 months. Also offers extensive protection for components stored outdoors, both covered and uncovered.

APPLICATION

Use as received – apply by spray, brush or dipping in a well-ventilated area. Leaves a thin waxy film on drying.

For best results apply sparingly to avoid excessive product build-up.

BENEFITS

- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces.
- Compatible with both ferrous and non-ferrous metals.
- Outstanding corrosion protection properties.
- Excellent penetration qualities.
- Non-staining formulations.
- Provide exceptional medium to long term protection of metal components when stored undercover.
- Ideal for protection of metal stocks, agricultural machinery etc.

PERFORMANCE PROFILE

Indoor Protection	30 Months
Outdoor Protection Covered	18 Month
Outdoor Protection Uncovered	Not Recommended

TYPICAL PROPERTIES

Appearance	Amber fluid
Specific gravity @15°C	0.820
Flash Point (COC)	38°C
Non-volatile residue	36%
Film thickness	4-6 microns

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.