# **SIAIR** Lubricants

SYNGEAR MTF 75W FE is a full synthetic, premium quality manual transmission fluid formulated with the very latest additive technology to offer high levels of gear protection and to promote enhanced fuel economy. Designed to be especially suitable for a wide range of modern passenger car transmission requirements.

## **APPLICATION**

Formulated for applications where a low viscosity, fuel efficient API GL-4 gear oil is specified. Particularly recommended for use in many modern passenger car manual transmissions from a wide range of manufacturers as listed below.

### **BENEFITS**

- Exceptional low temperature performance to provide protection even in extreme cold environments.
- Fuel-efficient formulation designed to offer reduced fuel consumption capabilities.
- Formulated to offer high load-carrying capability for superior bearing and gear protection.
- Excellent cleanliness, with enhanced anti-corrosion and anti-oxidation performance.
- Wide range of applications gives true multi-vehicle capability to help reduce stocks/inventories.

#### **PERFORMANCE PROFILE**

Suitable for use where the following are specified by the manufacturer;

- API GL-4
- MTF BOT 303, 350 M3
- MTF JWS 2271
- BMW MTF LT-3
- FIAT 9.55550-MZ2, MZ6
- FORD M2C 200-E1
- FORD M2C 200-D3
- FORD M2C 200-D2 (dry DCT)
- GM 1940004
- GM 19259104, 19259105
- NISSAN LV MTF-1
- NISSAN 32001 1BY0A
- PSA B71 2316 (HBVFE)
- PSA Standard 9730A8
- TOYOTA/LEXUS 08885-81001
- TOYOTA/LEXUS 08885-81081
- VOLVO 1161838, 1161839
- VW G 052 512 (dry DCT)
- VW G 052 171, G 052 178
- VW G 052 527, G 055 512
- VW G 052 726, G 060 726
- VW G 052 529, G 055 529
- VW G 052 726, G 009 317
- VW G 060 726, G 070 726

### **TYPICAL PROPERTIES**

Density @ 15.6°C 0.845

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD) Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk Registered in England: 05866783 VAT Registration No: 889171963

# **SIAIR** Lubricants

Viscosity@ 100°C	6.4 cSt
Viscosity @ 40°C	36.3 cSt
Viscosity Index	160

# **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD) Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk Registered in England: 05866783 VAT Registration No: 889171963