SYNMAX SPECTRUM 5W-30

Last Updated: 09.01.2025
Product Code: AE08018

SYNMAX SPECTRUM 5W-30 is a full synthetic mid SAPS (Sulphated Ash, Phosphorus and Sulphur) engine oil suitable for use with the latest technology in both petrol and diesel engines.

APPLICATION

Formulated for use in a wide range of passenger cars and light commercial vehicles with both petrol and diesel engines where a 5W-30 lubricant of ACEA C2 or ACEA C3 quality is required.

Especially recommended for workshop use where many different vehicle types are serviced, including vehicles fitted with Diesel Particulate Filters and Three Way Catalysts and those meeting Euro IV and V emissions standards.

BENEFITS

- Satisfies a wide range of vehicle requirements and applications.
- Excellent thermal stability.
- Provides critical protection during cold starts.
- Mid SAPS (Sulphated Ash, Phosphorus and Sulphur) technology to protect DPF and TWC systems.
- Improved fuel economy characteristics.
- Stay-in-grade properties offer full engine protection even at high running temperatures.

PERFORMANCE PROFILE

- ACEA C2, C3
- API SN, SM
- MERCEDES-BENZ 229.31
- GM DEXOS 2TM

Suitable for many modern vehicles from marques such as Peugeot, Citroen, Honda, Infiniti, Toyota, Lexus, Chrysler, Jeep, Dodge, FIAT, Alfa Romeo, Lancia, Hyundai, KIA, Subaru and Suzuki, as well as the specified manufacturer requirements listed above. Also suitable for use in many older BMW and MINI vehicles where this specification of lubricant is required.

In case of doubt, please refer to vehicle handbook to ensure correct oil requirement.

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C	11.6
Kinematic Viscosity @ 40°C	68.9
Viscosity Index	164
TBN (mg/KOH/g)	7.5
Density @ 15.6°C	0.847
Sulphated Ash, (%)	≤ 0.8

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963