

SYNMAX STELLAR 5W-30

Last Updated: 14.05.2025
Product Code: AE08038



SYNMAX STELLAR 5W-30 is a full synthetic mid SAPS (Sulphated Ash, Phosphorus and Sulphur) engine oil formulated with advanced performance technology suitable for use with the latest designs of petrol and diesel engines.

APPLICATION

Formulated primarily to meet the stringent requirements of Stellantis FPW 9.55535.03 specification for use in many Stellantis Group engines, including the DV5R (1.5ltr) and DW12RU (2.2ltr) diesels and the EB2DT and EB2ADT (1.2ltr) petrol engines found in many Peugeot, Citroen, DS and Vauxhall/Opel passenger cars and light commercial vehicles.

BENEFITS

- Built-in LSPI protection prevents premature combustion in smaller petrol engines.
- Outstanding oxidation and thermal stability.
- Excellent low temperature capabilities provides critical protection during cold starts.
- Low Sulphur, Ash and Phosphorous technology to protect DPF and TWC systems.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SN, SM, SL
- ACEA C2, C3
- GM Dexos 2
- MERCEDES-BENZ 229.52, 229.51, 229.31
- PSA B71 2297, B71 2290
- STELLANTIS FPW 9.55535.03

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.846
Kinematic Viscosity @ 100°C (cSt)	11.8
VI	183
Sulphated Ash (%)	max 0.8

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.