TRANSPLUS Z 75W-80

Last Updated: 09.01.2025
Product Code: AG0620

TRANSPLUS Z 75W-80 is a premium quality, full synthetic heavy-duty transmission oil using the latest additive technology.

APPLICATION

Formulated for use in many modern truck and bus transmissions, and especially suitable for modern heavy-duty ZF transmissions.

BENEFITS

- Synthetic base oil and optimized formulation for long service periods.
- Low viscosity and special friction properties to minimize power loss and improve fuel economy.
- Compatible with conventional and carbon based synchromesh materials.
- Controlled friction characteristics giving smooth gear changes and reduced synchronizer wear.
- Anti-pitting and wear protection to ensure long transmission life.

PERFORMANCE PROFILE

Suitable for use where the following requirements are specified;

- API GL-4 / GL-4S
- ZF TE-ML 02L
- MAN 341 Type E3, Z4
- VOLVO 97305, 97307 (i-Shift requirement)
- EATON extended drain
- DAF requirement

TYPICAL PROPERTIES

Viscosity @ 100°C (cSt)	9.5
Viscosity @ 40°C (cSt)	57.0
Viscosity Index	150
Density @ 15.6°C	0.848
Pour Point °C	-43

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963