TURBOLUBE HD 10W-40

Last Updated: 09.01.2025
Product Code: AE0733

TURBOLUBE HD 10W-40 is a semi-synthetic engine oil formulated to be suitable for many cars and light commercial vehicles, with either turbocharged or normally-aspirated engines.

APPLICATION

Recommended for use in many older petrol and diesel vehicles, as well as vehicles powered by LPG, where this specification of oil is required.

BENEFITS

- Suitable for use in multi-valve engines with hydraulic lifters where this grade of oil is specified.
- Provides easy starting and quick circulation in cold conditions.
- Excellent anti-wear properties.
- Promotes longer oil drain periods where appropriate.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SG/CF-4

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.867
Kinematic Viscosity @ 100°C	13.6
Kinematic Viscosity@ 40°C	89.9
V.I.	152
Flashpoint (COC) °C	205
Pour Point °C	-30

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963