TURBOPLUS 10W-40

Last Updated: 22.04.2026
Product Code: AE0669

TURBOPLUS 10W-40 is a heavy-duty semi-synthetic engine oil designed to meet the requirements of fleets operating across the full spectrum of vehicle types. Suitable for both diesel and petrol engines which do NOT require a low SAPS lubricant.

APPLICATION

Designed primarily for heavy-duty use in Euro 4* European trucks and buses, as well as many other types of commercial vehicles, including off-road machinery and other equipment which require this performance level. It is ideally suited to heavy-duty, long-distance trunking as well as the demands of use in light commercial vehicles, including small vans.

*NOTE – Not for use in Euro 4 vehicles requiring low SAPS lubricants. For vehicles requiring this specification of oil, use Synmax Perseus 10W-40 or Synmax Scorpio 10W-40

BENEFITS

- Semi-synthetic 10W-40 formulation ensures easier starting from cold compared to older 15W-40 oils.
- Capable of achieving maximum oil drain periods, both in and out of warranty.
- Formulated to provide superior protection against the effects of increased levels of carbon contamination in Euro 4 emission-controlled engines.
- API SL / ACEA A3 petrol engine specifications ensures mixed fleet status.
- Heavy-duty long distance trunking and stop / start delivery vehicles are protected under the umbrella of one oil for applications where these performance requirements are specified.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API CI-4/SL
- ACEA E7, E5, A3/B4
- Mercedes-Benz 228.3
- MAN 3275
- Deutz DQC III-10
- VOLVO VDS 3
- MACK EO-M+
- Cummins CES 20076 / 20077 / 20078
- Daimler Truck DTFR 15B110

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C (cSt)	16.0
Kinematic Viscosity @ 40°C (cSt)	106.0
SG @ 15.6°C	0.876
Viscosity Index	162
Flash Point (COC)	190°C
TBN (mgKOH/g)	10.7

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our

product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963