VACUUM PUMP OIL 320

Last Updated: 09.01.2025
Product Code: IV0324

VACUUM PUMP OIL 320 is a high quality vacuum pump oil formulated from highly refined mineral oils and suitable for lubricating most types of rotary and slide vane vacuum pumps.

APPLICATION

Use as received for rotary and slide vane vacuum pumps.

BENEFITS

- Excellent oxidation stability.
- Natural resistance to oil degradation.
- Resistant to sludge and deposit formation.
- Ensures rust protection to component parts.
- Good demulsibility keeps moisture and water in the oil to a minimum.

TYPICAL PROPERTIES

Kinematic Viscosity (cSt) @ 40°C	288 – 352
Kinematic Viscosity (cSt) @ 100°C	25.1
Viscosity Index	101
Density @ 15.6°C	0.900 – 0.950
Flash Point (COC) °C	>240
Pour Point °C	-8
Vapour Pressure kPa @ 20°C	<0.1

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963