

Last Updated: 13.06.2016
Code: AF0560

ENDURANCE LONG LIFE ANTIFREEZE is an ethylene glycol-based engine coolant concentrate. The modern formulation utilises Organic Acid Inhibitor Technology and is free from nitrites, amines, phosphates, borates and silicates.

APPLICATION

Endurance Long Life Antifreeze is designed to operate in coolant systems in passenger cars, light and heavy commercial vehicles as well as off-highway plant. When used at the recommended concentrations, the OAT formulation provides effective corrosion protection for up to 250,000km (over 150,000 miles) in passenger cars and up to 500,000km (over 300,000 miles) in commercial vehicles, or up to 5 years whichever is the sooner. A 50% dilution rate is recommended in the absence of advice from the OEM.

BENEFITS

- Protects from frost damage down to -40°C at 50% of total coolant volume.
- Exceptional corrosion protection giving extended life of up to 5 years.
- Free from nitrites, amines, phosphates, borates and silicates in accordance with many OEM requirements.

PERFORMANCE PROFILE - Meets the requirements of the following standards and specifications:-

- | | | |
|--------------------------|-------------------------|---|
| • BS 6580:2010 | • John Deere H24 B1/C1 | • RENAULT 41-01-001-D |
| • ASTM D4985, D3306 | • Mack 014GS 17004 | • VAG G12/G12+, TL 774-D/F |
| • Chrysler MS 9176 | • MAN 248, 324 Type SNF | • VOLVO PENTA VCS |
| • Cummins 85T8-2, 90T8-4 | • Mercedes-Benz 325.3 | • Suitable for use where G30, G33 and G34 specification fluids are required. |
| • FORD WSS-M97B44-D | • MTU MTL 5048 | |
| • GM/Saab 6277M, 1899M | • PSA Group B71 5110 | |

SOLUTION - % VOLUME	FREEZE POINT PROTECTION	S.G. READING
25%	-12°C	1.030
33%	-22°C	1.045
50%	-40°C	1.087

TYPICAL PROPERTIES

Appearance: Red/Orange Colour

Conforms to British Standard BS 6580:2010

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.