

Last Updated: 08.07.2016
Code: AF0056

UNIVERSAL ANTIFREEZE 50:50 is a high quality ethylene glycol-based pre-mixed engine coolant. The formulation utilizes established inhibitor technology and is free from nitrites, amines and phosphates.

APPLICATION

The pre-mixed 50% formulation is as recommended by most vehicle manufacturers, and is designed to be used as received to provide effective corrosion and frost protection for up to 2 years. Formulated for compatibility with coolant systems in passenger cars, light and heavy commercial vehicles as well as off-highway plant which require this specification of coolant.

BENEFITS

- Suitable for use as a general purpose coolant in most vehicles.
- Provides cold weather and corrosion protection for up to 2 years.
- Free from nitrites, amines and phosphates.

TYPICAL PROPERTIES

| | |
|--------------------------------|--------------|
| Appearance: | Blue liquid |
| Conforms to British Standard: | BS 6580:2010 |
| Freeze Point Protection: | -40°C |
| Specific Gravity: | 1.06-1.075 |
| pH Value 50% Aqueous Solution: | 7.8 |

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.