

Last Updated: 05.10.2020

Code: AD0068

AUTOTRANS MV is a premium, multi-vehicle, fully synthetic fluid primarily designed to meet the exacting requirements of the latest automatic transmissions of Asian/Far Eastern origin found in many Japanese and Korean vehicles.

APPLICATION

Especially formulated to meet the latest requirements of manufacturers such as **HONDA, MAZDA, MITSUBISHI, NISSAN, TOYOTA, KIA** and **HYUNDAI**, as well as many European OEM's using **JATCO** and **Aisin Warner** transmissions of the same origin, such as **JAGUAR, LAND ROVER** and **VW/AUDI**, and suitable for use where **GM Dexron VI** fluid is specified.

BENEFITS

- Outstanding anti-wear protection to extend transmission life.
- Offers smooth shift quality even in extreme low temperature environments.
- Extended oil durability offers longer change interval capability.
- Exceptional fluidity throughout the high-low temperature range.
- Formulated to maintain viscosity and film strength even during high temperature operation.
- Compatible with all types of seal materials.
- Excellent oxidation and thermal resistance for longer component and fluid life.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- **GM** Dexron VI
- **FORD** Mercon-LV
- **FORD** M2C 922-A1 for Durashift 5F31J
- **JASO** M315 Class 1A
- **AISIN WARNER** AW-1, F21
- **ATF** JWS 3309, 3324, N402
- **JATCO** K17, 3100 PL085
- **BMW** 83 22 0 397 114
- **BMW** 83 22 2 163 514
- **Chrysler/Jeep** MS 9602
- **Chrysler/Jeep** ATF +4
- **HONDA** DW-1, Z1
- **HYUNDAI/KIA** SP-IV, SPH-IV
- **HYUNDAI/KIA** Red-1K
- **HYUNDAI/KIA** 040000C90SG
- **HYUNDAI/KIA** JWS 3309 T-4
- **HYUNDAI/KIA** NWS-9638 T-5
- **JAGUAR** ATF 3100 PL085,
- **JAGUAR** ATF K17
- **LAND ROVER** LRN402
- **LAND ROVER** AWS3309
- **LAND ROVER** LR002748
- **MAZDA** FZ
- **MITSUBISHI** ATF-J3
- **NISSAN** Matic S, N402
- **SAAB** 93 165 147
- **SUBARU** ATF-HP
- **SUZUKI** ATF 3314, 3317
- **TOYOTA/LEXUS** WS
- **TOYOTA/LEXUS** JWS 3324
- **VOLVO** 97342 (AT102)
- **VOLVO** 1161540, 1161640
- **VW/AUDI** G 055 540
- **VW/AUDI** G 055 025
- **VW/AUDI** G 052 533
- **VW/AUDI** G 052 990
- **Not recommended for CVT or DCT transmissions**

TYPICAL PROPERTIES

Appearance: Red Kinematic Viscosity @ 100°C (cSt): 6.3 (typical)
Specific Gravity @ 15.6°C: 0.850

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)

Gill Bridge Oil Works, Lowlands Road, MIRFIELD,
West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371

Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk

Registered In England: 05866783 VAT Registration No: 889171963



Cert. Number 12669
ISO 9001