

Last Updated: 20/01/2016

Product Codes: CL0085, CL0080, CL0337, CL0081, CL0120, CL0465

**COMPRESSOR OILS 22, 32, 46, 68, 100 & 150** are a range of oils designed for the lubrication of reciprocating and rotary compressors, and meet the requirements of most vane compressors for 2000 hour services.

## APPLICATION

Use as received for the lubrication of reciprocating and rotary compressors.

## BENEFITS

- Effective control of carbon deposits and sludge formation.
- Carefully selected refined mineral oils ensure resistance to oxidation.
- Resists emulsification.
- Helps prevent filters from blocking.
- Minimises equipment downtime.
- Suitable for high discharge temperature equipment.

## TYPICAL PROPERTIES

	ISO 22	ISO 32	ISO 46	ISO 68	ISO 100	ISO 150
SAE Viscosity No.	10	15	20	20	30	40
Viscosity @ 40°C	20.5	31.5	46.4	67.7	103	143
Viscosity @ 100°C	4.3	5.5	6.5	8.9	11.3	14.2
Density	0.864	0.877	0.883	0.887	0.891	0.885

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.