

Last Updated: 30.10.2020
Code: AD0075

DRIVE TRAIN FLUID TO-4M is a multi-season lubricant utilising a very high performance, semi synthetic multigrade formulation. Primarily designed for use in transmissions, final drives and hydraulic systems which require a fluid meeting the exacting performance demands of Caterpillar TO-4M and ZF TE-ML 03C requirements.

BENEFITS

- Exceptional friction control to prevent clutch slippage and greatly improve the quiet and efficient action of transmissions and brakes.
- Superior wear protection and load carrying capabilities.
- Outstanding yellow metal protection.
- Greatly extended drive line component life.
- Enhanced wet brake performance profile.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API GL-4
- Caterpillar TO-4M, TO-4
- Allison TES-439, C-4 (off road)
- ZF TE-ML 03C

TYPICAL PROPERTIES

Appearance:	Dark amber liquid
Density @ 15.6°C:	0.871
Kinematic Viscosity @ 100°C (cSt):	14.1
Pour Point °C:	-38

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.