Technical Data Sheet

SAR Lubricants

Last Updated: 08.01.2016 Code: AG0084

EP GEAR OIL 80w90 GL-4 is a blend of high quality, solvent refined mineral base stocks combined with selected performance additives.

APPLICATION

Use as received for applications requiring an API GL-4 extreme pressure gear and transmission lubricant.

BENEFITS

Specially selected additives combined with high quality solvent refined base stocks with EP performance.

- Primarily designed for use in vehicle gearboxes
- Excellent protection from wear
- Industrial units requiring API GL-4 recommendations
- Industrial power units
- Can be used in axles <u>not</u> requiring hypoid oils

TYPICAL PROPERTIES

- API GL-4
- SAE 80w90
- MIL-L-2105

- Density @ 15°C: 0.894
- Viscosity @ 100°C: 18.4 cSt

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAPT LUBPHUANTS (SOURE A. RADOURE & SONS LTP) Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

