Technical Data Sheet

SAR Lubricants

Last Updated: 22.06.2016 Product Code: AE0448

FULL SYNTH TWO STROKE is a very high performance, fully synthetic, ashless two stroke oil which utilises the very latest additive technology, together with a balanced combination of synthetic base oils to meet the severe requirements of JASO FD specification, as well as modern demands for an ashless, multi-purpose oil suitable for use in a variety of applications.

APPLICATION

Latest technology makes it suitable for both air- and water-cooled two stroke engines in modern scooters, mopeds and motorcycles, and is compatible with both pre-mix and oil injection systems. The balanced formulation makes it also suitable for use in a wide variety of other applications such as chainsaws, lawnmowers etc. especially where a modern, ultra-low-smoke full synthetic grade is specified.

Can be mixed with petrol in ratios between 1:75 and 1:25, but please follow equipment manufacturers guidelines and recommendations.

BENEFITS

- Ultra-low-smoke formulation.
- Conforms to the strict requirements of JASO FD specification, with far higher detergent levels than JASO FC.
- Higher detergency reduces combustion chamber deposits to prevent power loss and pre-ignition.
- Enhanced protection against cylinder and piston scuffing.
- Very high film strength for ultimate engine protection.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- JASO FD
- API TC
- ISO-L-EGD

TYPICAL PROPERTIES

Appearance:	Red	Specific Gravity @ 15.6ºC:	0.871
Kinematic Viscosity @ 100°C:	8.2	Flash Point OC:	140

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAR LUBRICANTS (Source A, RADGLIFFE & SONS LTD) Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

> 12669 ISO 9001

