

Last Updated: 04.02.2021  
Product Codes: AG0640

**MULTIVEHICLE MTF 75w80 GL-4+** is a fuel-efficient, manual transmission fluid formulated with the very latest additive technology to offer high levels of gear protection and synchronizer compatibility. Designed to be especially suitable for a wide range of modern passenger car transmission requirements where gearbox and differential share the same unit.

## APPLICATION

Formulated for applications where an API GL-4 or GL-4+ gear oil of this viscosity is specified. Particularly recommended for use in many modern passenger car manual transmissions from a wide range of manufacturers as listed below.

## BENEFITS

- Proven synchronizer protection far in excess of standard API GL-4 specification fluids.
- Fuel-efficient formulation with exceptional low temperature performance.
- Formulated to offer high load-carrying capability for superior bearing and gear protection.
- Excellent cleanliness, with enhanced anti-corrosion and anti-oxidation performance.
- Wide range of applications gives true multi-vehicle capability to help reduce stocks/inventories.

## PRODUCT APPLICATION – API GL-4 and API GL-4+

Suitable for use where the following are specified by the manufacturer;

- **BMW** MTF LT-2, LT-3
- **BMW** MTF LT-4
- **BOT** 350 M3
- **GM** 1940004, 1959104
- **GM** 1940764, 1940768
- **GM** 1940182
- **GM** W16612 (dry DCT)
- **FIAT** MZ1, MZ6, MZ7
- **FORD** M2C 186-A
- **FORD** M2C 200-C
- **FORD** M2C 200-D2 (dry DCT)
- **Honda** Special MTF, MTF-II
- **Honda** MTF-III
- **Nissan** MT-X
- **Nissan** MT-XZ TL (JR Type)
- **PSA** B71 2330 (EZL 848)
- **PSA** B71 2315
- **PSA** B71 2316 (HBVFE)
- **Renault** DC4 DWS (dry DCT)
- **Volvo** 97308, 97309
- **VW** G 052 512 (dry DCT)
- **VW** G 055 512 (dry DCT)
- **VW** G 052 171, G 052 178
- **VW** G 052 726, G 060 726
- **VW** G 50, G 009 317
- **VW** G 052 527 A2
- **VW** G 070 726 A2

Also suitable for most passenger car manual transmissions as specified by the manufacturers listed below;

- Alfa Romeo/FIAT
- Chrysler/Jeep/Dodge
- Hyundai/KIA
- Jaguar Land Rover
- Mazda
- Mercedes-Benz/SMART
- Mitsubishi
- Renault/Dacia
- Suzuki
- Toyota

## TYPICAL PROPERTIES

Density @ 15.6°C:	0.855	Viscosity @ 40°C:	50.9 cSt
Viscosity @ 100°C:	8.9 cSt	Viscosity Index:	156

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.