# **Technical** Data Sheet

## **SAR** Lubricants

Last Updated: 02.07.2018 Product Code: IF 0405

**MULTIGRIND NF400** is a fully synthetic grinding fluid concentration.

#### **BENEFITS**

- Formulated to promote enhanced protection against bacterial and fungal degradation.
- Exceptional cooling properties.
- Good wheel flushing properties
- Excellent corrosion protection of machine and work pieces.
- Nitrite, phenol and chlorine free.

#### **APPLICATIONS**

(Minimum treat rate: 3% in water)

Typical concentration for cylindrical, centre-less and surface grinding	3% - 4%
For more arduous applications and hard water areas increase up to	5%

Water hardness should be checked to determine optimum running concentrations, please consult your SAR Lubricants Sales Engineer for further details.

### TYPICAL PROPERTIES

Appearance Specific Gravity @ 15.6°C pH (3% solution) Amber / Green Clear Solution 1.03 8.7

Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963



Cert. Number 1266

# **Technical** Data Sheet



### **FLUID MAINTENANCE**

Refractive Index: - 2.94 = % / ° Brix

Refractometry data for Multigrind NF400		
Refractometer reading	Actual Concentration	
0	0	
0.34	1.0	
0.51	1.5	
0.68	2.0	
0.85	2.5	
1.02	3.0	
1.19	3.5	
1.36	4.0	
1.53	4.5	
1.70	5.0	
1.87	5.5	
2.04	6.0	

### **HEALTH & SAFETY, STORAGE AND DISPOSAL**

**MULTIGRIND NF400** should be stored in dry conditions and protected from extreme temperatures: between 4°C and 35°C is the recommended storage temperature.

**MULTIGRIND NF400** is unlikely to present any significant health or safety hazard when used as recommended by SAR Lubricants. Good standards of personal and industrial hygiene are to be maintained by the user (see Material Safety Data Sheets). In order to protect the environment, the product used should be safely disposed by a licensed contractor. The packaging material should be handled by a recognised reconditioning firm.

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT.

SAR Lubricants assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of SAR Lubricants

Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

