

Last Updated: 09.09.2016

Product Code: RING20S; RING32S; RING 32; RING 46; RING 68; RING 100

**RING OILS** are formulated for the lubrication of a wide variety of spinning and twisting rings including sintered rings.

## APPLICATION

Use as received for the lubrication of ring spinning including solid and sintered rings.

## BENEFITS

- Different viscosities available for different yarn counts.
- Excellent oxidation and wear resistance.
- Scourable properties ensure easy removal from fabric.
- Selected additives promote clear running.
- RING OIL 20S and 32S are synthetic based fluids and also contain EP additive.

## TYPICAL PROPERTIES

	RING OIL 20S	RING OIL 32S	RING OIL 32	RING OIL 46	RING OIL 68	RING OIL 100
Appearance	Pale Straw Oil	Pale Straw Oil	Pale Amber Oil	Pale Amber Oil	Pale Amber Oil	Pale Amber Oil
Specific Gravity @ 15.6°C	0.850	0.867	0.870	0.890	0.892	0.898
Viscosity @ 40°C	19.8-24.2 cSt	28.8-35.2 cSt	28.8-35.2 cSt	41.4-50.6 cSt	61.2-74.8 cSt	90-100 cSt
Pour Point	Below -20°C	Below -20°C	Below -5°C	Below -5°C	Below -5°C	Below -5°C
Cloud Point	> 70°C	> 70°C	> 70°C	> 70°C	> 70°C	> 70°C
Moisture	0.5%	0.5%	0.5%	0.5%	0.5%	0.5%

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.