

Last Updated: 20.05.2014

Product Code: IP0542

SARCOAT WF is a high quality, wax film rust preventative formulated with a combination of dewatering additive technology together with film-forming corrosion prevention capabilities to provide extensive long-term protection.

APPLICATION

Use as received – it is recommended that the product is stirred well before use. In low temperatures, product may gel, but will return to normal consistency under standard working conditions. Apply by spray or brush in a well-ventilated area. Leaves a firm, waxy film on drying.

BENEFITS

- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces, before leaving a firm, waxy deposit on drying.
- Offers exceptional long-term corrosion protection indoors for over 2 years, and up to 2 years for components stored outdoors.
- Compatible with all types of ferrous and non-ferrous metals.
- Excellent penetration qualities to protect normally inaccessible areas.
- Ideal for long term protection of all metal stocks and agricultural machinery, as well as both car and commercial vehicle panels, underbodies etc. especially during storage and restoration.

TYPICAL PROPERTIES

Appearance:	Brown fluid
Film thickness:	33 microns
Flash Point (COC) :	>38°C
Indoor protection:	>2 years
Outdoor protection:	<2 years

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.