Technical Data Sheet

SAR Lubricants

Last Updated: 21.11.2017 Product Code: MW0930

SARDRAW 2204 is a custom blend of mineral oils and selected additives designed for use in heavy duty metal forming and drawing operations.

(Product formerly known as SARFORM 2204)

APPLICATION

A metal working fluid for use in severe metal forming and drawing operations on steel and steel alloys. Typically used in blanking operations, sheet metal forming and similar applications.

BENEFITS

- Pale colour
- Low odour and operator acceptability
- Contains chlorinated EP additives
- Corrosion inhibitor pack
- Medium viscosity
- High lubricity
- Enhanced anti-misting properties, so user friendly.

TYPICAL PROPERTIES

Appearance	Amber liquid
Kinematic Viscosity @ 40°C	61.2 - 74.8 cSt
Specific Gravity @ 15.6 [°] C	0.965

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SART LUBRIGANTS (SOURE A. RADOURE & SONS LTD) Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

