

SARFORM BIO is a customised blend of natural vegetable oils and esters which produces a readily biodegradable mould release oil.

APPLICATION

Supplied ready for use, and should be applied as evenly as possible for optimum performance. Application may be by either brush, roller, swab or spray, (use appropriate respiratory protection if spraying). For most economical performance, application by fine spray is recommended. Avoid excessive build-up of product, especially in tight angles. For new 'unsealed' formwork, pre-treatment is recommended before applying a second coat.

BENEFITS

- Suitable for use on all formworks, concrete and brick.
- No unpleasant odours.
- Designed to show effective rust inhibiting properties.
- Biodegradable formulation does not contain hydrocarbon solvents – VOC free.
- Operator-friendly in use for reduced issues with sensitive skin.
- Continued use gives progressively better results on timber formwork.
- Can be used with white or grey cements, as well as concretes containing pigments.
- Drastically reduces the risk of blowholes, staining and surface blemishes.

TYPICAL PROPERTIES

Appearance	-	Pale amber liquid
Specific Gravity @ 15°C	-	0.905
Viscosity @ 40°C	-	6.5 cSt
Setting Point	-	4°C

STORAGE

SARFORM BIO is a natural oil-based product and should be protected from frost. Normal shelf life - up to 6 months when stored in manufacturer's sealed containers.

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.