Technical Data Sheet

SAR Lubricants

Last Updated: 30.11.2016 Product Code: CM0092

SARFORM F is a high quality mould release agent, formulated with a customised blend of selected mineral based components, solvents and additives.

APPLICATION

Suitable for use for in brick and concrete forming applications. Use as received, application may be by either brush, roller or spray, (use appropriate respiratory protection if spraying). Avoid excessive build-up of product, especially in tight angles.

BENEFITS

- Produces good surface finish
- Excellent separation properties
- Ease of application
- Blemish free products

TYPICAL PROPERTIES

Appearance	-	Pale yellow liquid
Specific Gravity @ 15 ⁰ C	-	0.840
Viscosity @ 40°C	-	6 cSt
Flashpoint ^o C	-	>70

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAPT LUBPHUANTS (SOURE A. RADOURE & SONS LTP) Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963



Cert. Number 1266