

Last Updated: 25.07.2013

Product Code: IO0702

SARLUBE 95 BRIGHTSTOCK

TYPICAL PROPERTIES

| TESTS, UNITS | METHODS | SPECIFICATION | RESULTS |
|-------------------------------------|-------------|---------------|---------|
| Colour ASTM | ASTM D 1500 | | 4.5 |
| Density @ 15.0°C, kg/m ³ | ASTM D 4052 | | 900.2 |
| Flash Point COC, °C | ASTM D 92 | | 280 |
| Pour Point, °C | ASTM D 97 | | - 12 |
| Sulphur Content, %wt | ASTM D 2622 | | 0.436 |
| Viscosity Kinematics @ 40°C cSt | ASTM D 445 | | 460 |
| Viscosity Kinematics @ 100°C cSt | ASTM D 445 | | 28.12 |
| Viscosity Index | ASTM D 2270 | | 90 |
| Water Content | ASTM D 6304 | | 53 |

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.