

Last Updated: 15.02.2016

Product Codes: IO0194, IO0112, IO0110, IO0032, IO0031
IO0258, IO 0403, IO 0113, IO 0439, IO 0248

SARLUBE OILS are a range of general purpose machine lubricants manufactured from a blend of solvent refined mineral oils.

APPLICATION

Use as supplied where non-additive lubricants are specified, such as gearboxes and similar light applications.

BENEFITS

- Excellent lubricity
- API GL1

TYPICAL PROPERTIES

	22	32	46	68	100	150	220	320	460
Physical Form	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
Colour	Pale Yellow	Pale Amber	Pale Amber	Amber	Amber	Amber	Amber	Dark Amber	Dark Amber
Odour	Oily	Oily	Oily	Oily	Oily	Oily	Oily	Oily	Oily
Boiling Point (°C) Typical	218	220	225	225	230	> 230	> 230	> 230	> 230
Viscosity @ 40°C (cSt)	18.9 - 22	28.8 - 35.2	41.4 - 50.6	61.2 - 74.8	90 - 110	135 - 165	198 - 242	288 - 352	414 - 506
Flashpoint °C (C.C.)	193	197	200	210	220	223	232	240	255
Density @ 15.6°C	0.863	0.875	0.880	0.882	0.885	0.887	0.889	0.894	0.905

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.