

SYNMAX 5w40 is a high-performance, full synthetic engine oil designed for use in both petrol and diesel engines. Specifically designed for modern passenger cars and light commercial vehicles which require a Normal SAPS lubricant according to ACEA 2012 requirements.

APPLICATION

Recommended for use as a crankcase lubricant in all vehicles where a Normal SAPS oil of this grade is specified by the manufacturer.

In addition, the JASO MA2 specification makes it ideally suited for use in many modern high-performance motorcycles.

BENEFITS

- Latest additive technology offers exceptional wear protection even under extreme operating conditions.
- Provides quick circulation of the oil even under cold start conditions.
- Designed to maximise fuel economy and minimize emissions.
- Formulated to meet many OEM requirements and is also ACEA 2012 compliant.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SN/CF , ACEA A3/B4
- Mercedes Benz 229.3 (v 2012.2)
- VW 502.00; 505.00
- Porsche A40
- Renault RN 0700 / RN 0710
- FIAT 9.55535-Z2
- Vauxhall/Opel/GM LL-A-025/LL-B-025
- JASO MA2 (T903-2011)

TYPICAL PROPERTIES

Pour Point:	-40°C
Kinematic Viscosity @ 100°C:	12.5 < 16.3 cSt
TBN mg KOH/g (ASTM D-2896)	11.02

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.