Technical Data Sheet

SAR Lubricants

Last Updated: 17.06.2019
Product Code: AE08015

SYNMAX GENESIS 0w30 is a full synthetic, fuel efficient engine oil suitable for the latest generation of petrol and diesel engines fitted with exhaust after-treatment systems.

APPLICATION

Formulated primarily for use in **FORD** diesel passenger cars and light commercial vehicles/vans from 2014 onwards where a 0w30 engine lubricant requiring **FORD M2C-950A** specification is recommended.

It also carries official **JAGUAR/LAND ROVER** verification for engines which require oil to **STJLR.03.5007** standard.

Please note: *- this oil is not backwardly-compatible for use in applications where a 5w30 oil to meet earlier FORD specifications M2C-913A, M2C-913B, M2C-913C and M2C-913D are required.*

In case of doubt, please refer to vehicle handbook to ensure correct oil specification requirement.

BENEFITS

- Meets stringent **FORD** and **JAGUAR/LAND ROVER** requirements for modern Euro 6 engines requiring 0w30 oil.
- Provides additional protection against the adverse effects of using modern Bio Fuels.
- Greatly improved cold start properties even at very low temperatures.
- Stay-in-grade properties ensure low levels of volatility at high running temperatures.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- **ACEA** C2
- **FORD** M2C-950A
- **JAGUAR/LAND ROVER** STJLR.03.5007 - approved

TYPICAL PROPERTIES

Kinematic Viscosity @ 100^{0}C:	9.5	Flash Point ^{0}C:	>200
Density @ 15.6^{0}C:	0.840	TBN, mg/KOH/g:	8.2
Pour Point ^{0}C:	-46	Sulphated Ash, %:	<0.8

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, MIRFIELD,
West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371
Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk
Registered In England: 05866783 VAT Registration No: 889171963

Cert. Number 12669
ISO 9001