

TACK 320 is a high-quality oil formulated with selected additives to offer a combination of high film strength and substantial anti-fling capabilities.

APPLICATION

Recommended where the high film strength and anti-fling and characteristics are required to ensure correct lubrication without excessive oil loss. Especially recommended for chain saw cutter bars, textile machinery, chains, wire rope and open gear applications where these properties are desirable.

BENEFITS

Exceptionally high film strength and anti-fling capabilities to provide protection in the most demanding conditions
Formulated to offer excellent retention on components and provide minimum drainage from vertical surfaces
Maximum corrosion protection for chains, wire ropes and open gears

TYPICAL PROPERTIES

| | |
|------------------------------|-------------------------|
| Density @ 15°C: | 0.894 kg/m ³ |
| Kinematic Viscosity @ 40°C: | 320 cSt |
| Kinematic Viscosity @ 100°C: | 24.0 cSt |
| Flash Point (COC) °C: | 258 |

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.