Technical Data Sheet

SAR Lubricants

Last Updated: 20.04.2018 Product Code: AG0620

TRANSPLUS Z 75w80 is a premium quality, full synthetic heavy-duty transmission oil using the latest additive technology.

APPLICATION

Formulated for use in many modern truck and bus transmissions, and especially suitable for modern heavy-duty ZF transmissions.

BENEFITS

- Synthetic base oil and optimized formulation for long service periods.
- Low viscosity and special friction properties to minimize power loss and improve fuel economy.
- Compatible with conventional and carbon based synchromesh materials.
- Controlled friction characteristics giving smooth gear changes and reduced synchronizer wear.
- Anti-pitting and wear protection to ensure long transmission life.

PERFORMANCE PROFILE

Suitable for use where the following requirements are specified;

- API GL-4 / GL-4S
- ZF TE-ML 02L
- MAN 341 Type E3, Z4

- VOLVO 97305, 97307 (i-Shift requirement)
- EATON extended drain
- DAF requirement

TYPICAL PROPERTIES

Viscosity @ 100°C (cSt):	9.5	Density @ 15.6°C:	0.848
Viscosity @ 40°C (cSt):	57.0	Pour Point ⁰ C:	-43
Viscosity Index:	150		

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

Gill Bridge Oil Works, Lowlands Road, MIRFIELD, West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371 Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk Registered In England: 05866783 VAT Registration No: 889171963

