

TURBOLUBE 10w40 is a high performance, semi-synthetic engine oil formulated to meet today's demanding requirements.

APPLICATION

Suitable for use in all cars and light commercial vehicles where a 10w40 engine oil of this specification is required.

BENEFITS

- Provides easy starting and quick circulation in cold conditions
- Excellent anti-wear properties
- Promotes longer oil drain periods

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SL / CH-4
- ACEA A3/B4
- VW 500.00, VW 505.00
- Mercedes-Benz 228.1, 229.1
- Peugeot/Citroen PSA B71 2295
- Porsche specification

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C (cSt):	12.9	Viscosity Index:	171
Kinematic Viscosity @ 40°C (cSt):	76.0	Flash Point (COC):	190°C
SG @ 15.6°C:	0.878		

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.