

**FLEETLUBE 10w40** is a mixed fleet engine oil suitable for use in both petrol and diesel engines.

## APPLICATION

Suitable for use in all types of vehicles including heavy-duty diesels, light commercials, vans and cars, as well as agricultural equipment and off-highway vehicles where this specification of oil is required by the engine manufacturer.

Please note - Not suitable for vehicles meeting EURO 4 or later emission standards, and which require a low SAPS lubricant.

## BENEFITS

- High shear stability
- Promotes easy starting in cold conditions
- Suitable for both turbocharged and normally aspirated petrol and diesel engines
- Enhanced anti-wear performance for reduced engine wear
- Excellent sludge control for stop-go city motoring

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API CG-4/SJ
- ACEA E2
- Mercedes-Benz 228.1
- MAN 271

## TYPICAL PROPERTIES

Specific Gravity @ 15.6°C:	0.888	Flash Point COC (°C):	220
Kinematic Viscosity @ 100°C (cSt):	13.82	Pour Point (°C):	-32
Kinematic Viscosity @ 40°C (cSt):	95.51	TBN mg KOH/g:	9.18
VI:	147		

## HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.