

# **SAR** Lubricants

Last Updated: 23.10.2023 Product Code: AE08014

**SYNMAX ORION FE 5w30** is a full synthetic, fuel efficient, low SAPS (Sulphated Ash, Phosphorus and Sulphur) heavy duty diesel engine oil designed for the latest generation of heavy duty diesel engines.

#### **APPLICATION**

Especially suitable for the latest Euro 6 engines, and the extensive Performance Profile also enables coverage of mixed fleets, especially those with engines equipped with Diesel Particulate Filter (DPF) or catalytic after treatment system (such as SCR). Offers exceptional levels of engine protection even when operating with low-sulphur diesel fuel (50 ppm or below) and under severe heavy-duty conditions.

**Note:** Although not VOLVO VDS-5 or RENAULT RLD-5 approved, this product can be used where VOLVO VDS-5 or RENAULT RLD-5 specifications are required, but the oil drain interval should be amended accordingly.

#### **BENEFITS**

- Designed to promote low oil consumption and enhanced fuel economy capabilities.
- Full synthetic 5w30 formulation offers exceptional thermal stability and easier cold starts.
- Offers extended oil drain intervals thereby reducing maintenance costs.
- Formulated to reduce carbon contamination within engine crankcase and offer excellent piston cleanliness.

#### **PERFORMANCE PROFILE**

Suitable for use where the following specifications are required;

- ACEA E4, E7, E8, E11
- **ACEA** E6, E9
- API CK-4, CJ-4
- JASO DH-2
- SCANIA officially OEM confirmed to LDF-4
- MAN standard M3775
- MAN standard M3777
- MAN standard M3677 approved
- MAN standard M3477 approved
- MAN standard M3575 approved
- MAN standard M3271-1 approved

- Mercedes-Benz MB 228.52, 228.51
- Caterpillar ECF-3
- Cummins CES 20086, 20081
- **DAF** Euro 6 requirement
- Deutz DQC IV-18 LA
- IVECO 18-1804 Classe TLS E6 Euro 6 requirement
- MTU Type 3.1, 2.1
- Volvo VDS-4.5
- Renault RVI RLD-4/RLD-3
- Mack EO-S 4.5

### **TYPICAL PROPERTIES**

 Density @ 15°C:
 0.848
 Phosphorus (% Wt):
 0.8

 KV @ 100°C:
 11.9 cSt
 Sulphated Ash (% Wt):
 <1.0</td>

 Viscosity Index:
 168
 TBN:
 12.8

## **HEALTH & SAFETY**

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.









