

Last Updated: 28.11.2024

Product Code: AE08038

SYNMAX STELLAR 5w30 is a full synthetic mid SAPS (Sulphated Ash, Phosphorus and Sulphur) engine oil formulated with advanced performance technology suitable for use with the latest designs of petrol and diesel engines.

APPLICATION

Formulated primarily to meet the stringent requirements of **Stellantis FPW 9.55535.03** specification for use in many Stellantis Group engines, including the **DV5R (1.5ltr)** and **DW12RU (2.2ltr)** diesels and the **EB2DT** and **EB2ADT (1.2ltr)** petrol engines found in many **Peugeot, Citroen, DS and Vauxhall/Opel** passenger cars and light commercial vehicles.

Also suitable for use in other marques where a modern ACEA C2 or C3 grade is required. In case of doubt, please refer to vehicle handbook to ensure correct oil specification requirement.

BENEFITS

- Built-in LSPI protection prevents premature combustion in smaller petrol engines.
- Outstanding oxidation and thermal stability.
- Excellent low temperature capabilities provides critical protection during cold starts.
- Low Sulphur, Ash, and Phosphorus technology to protect DPF and TWC systems.
- Improved fuel economy characteristics.
- Stay-in-grade properties offer full engine protection even at high running temperatures.

PERFORMANCE PROFILE

- ACEA C2, C3
- API SN, SM, SL
- GM DEXOS 2™
- MERCEDES-BENZ 229.52, 229.51, 229.31
- PSA B71 2290
- PSA B71 2297
- STELLANTIS FPW 9.55535.03

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C: 11.8
Kinematic Viscosity @ 40°C: 64.0
Viscosity Index: 183

Density @ 15°C: 0.846
Sulphated Ash, (%): ≤ 0.8

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.